



# 100Tii40MTL **Tile Insert Drain**

All stainless steel drainage unit made to specified length with specified outlet position.

The 100Tii40 is a Tile Insert Drain manufactured from 3mm thick 316 marine grade stainless steel.

Suitable for tiles up to 25mm thick.


The maximum length of the tile insert will be 1200mm in one piece, channels longer than 1200mm will have inserts in multiple equal sections

#### **SPECIFICATIONS + DIMENSIONS**

**Channel Width Channel Depth** Length(s) **Outlet Size** 

106mm DN40, DN50, DN65, DN80, DN100

## STORMTECH COLOUR FINISHES



Electroplate finishes subject to natural variation with time and local environment. Factors such as pools/surf beaches may require electropolishing. Contact us for suitability.

## **PRODUCT APPLICATIONS**

**Bathroom Drainage** Aged / Health Care Drainage **Balcony Drainage Commercial Drainage** Courtyard / Patio Drainage Pool and Spa Area Drainage

Hospitality Drainage Paved Area Drainage Shower Drainage Multi-Residential Drainage Special Needs Drainage **Threshold Drainage** 

Copyright © Stormtech Pty Ltd. Patent 733361. Drawings not to scale, please use dimensions shown Downloaded 26/08/2025 (please check for updates)




Visit **stormtech.com.au** for tools + inspiration.

42mm As Required

ARCHITECTURAL **GRATES + DRAINS** 



Code 100Tii40MTL Range 100 Grate Style Ti Category Made-to-Length Channel Material Stainless Steel Steel Grade 316



Grates longer than 1500mm supplied in sections. Tile Inserts longer than 1200mm supplied in sections. Channels over 3000mm supplied in sections with joiner. +/-2mm tolerance on dimensions.